



P 10200 L P 10200 L/3SI P 10200 L/4SI

massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. / max. hydraulische Reichweite	8.00 m		9.92 m		11.86 m	
minimo sfilo idraulico / min. hydraulic outreach / min. alcance hidraulico / rallonge hydraulique min. / min. hydraulische Reichweite	4.14 m		4.22 m		4.26 m	
altezza massima / max height above installation level / altura max. desde el filo infer. de la base hauteur de levage au dessus du plan de pose / hubhöhe ab Fahrzeugrahmen	10.20 m		12.10 m		14.00 m	
portata gru base / outreach - lifting capacity / alcances hidraulicos - capacidad / extension - charge hydraulische Reichweite - Hubkraft	4.14 m 6.04 m 8.00 m	2450 kg 1600 kg 1170 kg	4.22 m 6.12 m 8.02 m 9.92 m	2210 kg 1410 kg 1020 kg 800 kg	4.26 m 6.16 m 8.06 m 9.96 m 11.86 m	2040 kg 1270 kg 890 kg 680 kg 550 kg
portata prolunga manuale / outreach with manual extens. - lifting capacity / alcances con prolongas manuales - capacidad / extension avec rallonges manuelles - charge Reichweite mit manuellen Verlängerungen - Hubkraft	10.05 m 12.10 m	800 kg 580 kg	11.97 m 14.02 m	570 kg 420 kg	13.91 m	410 kg
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada debit d'huile recommandé / Förderleistung der Hydraulikpumpe	30 l/min		30 l/min		30 l/min	
pressione di lavoro / working pressure / presión de trabajo / pression de travail / Betriebsdruck	270 bar		270 bar		270 bar	
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite Inhalt des Öltanks	50 l		50 l		50 l	
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / Schwenkbereich	402°		402°		402°	
coppia di rotazione / slewing torque / momento de giro / couple de rotation / Drehmoment	16 kNm		16 kNm		16 kNm	
altezza a riposo / height in folded position / hauteur en position repliee / altura en posición de reposo / Höhe ab Fahrzeugrahmen zusammengelegt	2200 mm		2200 mm		2200 mm	
larghezza a riposo / width in folded position / largeur en position repliee / anchura en posición de reposo / Breite zusammengelegt	2300 mm		2320 mm		2400 mm	
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers / peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl.-manuell seitlich ausziehbare Abstützungen	1440 kg		1590 kg		1740 kg	

- - - - - AREA DI LAVORO \ WORKING AREA
 ——— PORTATA CON LIMITATORE DI MOMENTO \ LIFT WITH LOAD LIMIT VALVE
 ——— PORTATA PROLUNGHE MANUALI \ MANUAL EXTENSIONS LIFT

Ing. BONFIGLIOLI S.p.A. BOLOGNA - ITALIA

tel 051/6867214 fax 051/6867222 e-mail: cranes@ingbonfiglioli.it